



NLR 757 – MEMBRANE Anti-Scalant

FOULING

The loss of membrane performance due to fouling by scaling components is common to many UF, NF and RO membranes worldwide. This fouling can lead to reduced permeate flow, changes in rejection characteristics across the membrane system, increases in differential pressure and frequent membrane cleaning or replacement.

CLEANING

Keeping your membrane clean with regular cleaning routines or performing a heavy duty maintenance cleaning to recover the membranes are possible solutions to overcome the fouling.

The NLR-757 liquid membrane anti-scalant is designed to target scaling foulants, silica, calcium and magnesium, as well as scaling metal complexes including iron. This pretreatment chemical will inhibit fouling to maintain the membrane performance and extend the frequency of cleaning.

The NLR-757 anti-foulant contains a unique blend of multiple prepackaged proprietary formula chemical ingredients.

USAGE INSTRUCTIONS

Usage for your particular system may require an individualized procedure based on your type of foulants. However, the following is a basic procedure that should work for a broad range of situations.

NLR-757 is a concentrated pretreatment chemical that should be used neat to the proper concentration. The anti-foulant solution should be kept in a clean tank or portable tote. You should use an appropriate metering pump to deliver the correct amount of anti-foulant to the feed tank or feed line prior to filtration. Here is a table outlining the volumes to use for various volumes.

Concentration	Usage	Volume of Water
2.5 ppm	0.015 GPH	100 gpm
5.0 ppm	0.030 GPH	100 gpm
10.0 ppm	0.060 GPH	100 gpm

The exact flow rate will depend on the size of your membrane module. YOU MAY NEED TO VARY THE CONCENTRATION TO FIND THE OPTIMUM AMOUNT TO ADD.

The more that is used as pretreatment, the longer you can run between full chemical cleanings. This is another parameter to consider when optimizing your process.

PACKAGING

NLR-757 is shipped as a liquid in 5-gallon plastic containers, 55-gallon drums, or 260 gallon totes. The shelf life when stored unopened indoors at a temperature between 5°C and 30°C is one year from its date of manufacture. For specific pricing and delivery information, please contact New Logic.

HANDLING

NLR-757 is an anti-scalant chemical and should not be mixed with other cleaners unless specified by the vendor.

Wear chemical resistant gloves when you expect long, constant exposure. It is also a good practice to wear safety glasses or goggles when using this product.